

Print date 2018-01-10

Revision date 2018-01-10

Revision number 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

1.1 Product Identifier

Product Type Welding powder
Product Name **Deloro 20 powder**
Product Code KSPN1064-1

Type powder

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use Industrial Manufacturing (all). Service life. cobalt and/or nickel containing alloys, steels, prefabricated parts and tools. Industrial use. Professional use. Wear and Corrosion Resistant Welding Consumable. Wear and Corrosion Resistant Components. Metallurgical Products. For use in industrial installations only.

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier Identification India: Kennametal India Limited 8/9th Mile, Tumkur Road Bangalore, Karnataka - 560073
bangalore.information@kennametal.com Phone: 1 800 10352271031
Singapore: Kennametal Pte Ltd. 3A International Business Park Unit #01-02/03/05
Singapore 609935 k-sg.sales@kennametal.com Phone: 1 800 622 1031
Pakistan: itsystem@brain.net.pk

Prepared By Kennametal Inc. 1600 Technology Way Latrobe, PA 15650, USA
E-mail k-corp-product.safety@kennametal.com
Company Emergency Phone Number Kennametal Security, Latrobe, US, PA +1-724-539-5610 (english)

1.4 Emergency telephone number

Emergency telephone number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

NRC (National Response Center) India, National Poisons Information Centre +91 112 659 36 77 or +91 112 658 93 91
Pakistan, National Poisons Control Centre +92 21 9920509/35686535
Philippines, National Poison Management & Control Center +632 524 10 78/+632 544 84 00/local 2311

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Skin Sensitization	Category 1
carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

2.2 Label Elements

Product Name Deloro 20 powder
Product Code KSPN1064-1



Signal Word	Danger
hazard statements	H317 - May cause an allergic skin reaction H351 - Suspected of causing cancer H372 - Causes damage to organs through prolonged or repeated exposure if inhaled
Precautionary Statements	P260 - Do not breathe dust/fume/gas/mist/vapors/spray P264 - Wash hands thoroughly after handling P270 - Do not eat, drink or smoke when using this product P273 - Avoid release to the environment P308 + P313 - IF exposed or concerned: Get medical advice/attention P280 - Wear protective gloves/protective clothing/eye protection/face protection P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
Precautionary Statements	P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking P271 - Use only outdoors or in a well-ventilated area P272 - Contaminated work clothing should not be allowed out of the workplace P285 - In case of inadequate ventilation wear respiratory protection P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention P363 - Wash contaminated clothing before reuse

2.3 Other Hazards

Warning

May cause sensitization by skin contact. Vapors may be irritating to eyes, nose, throat, and lungs. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Welding Hazards

CAUTION. Welding will create fumes which may be toxic. If welding is performed on plated or coated materials such as galvanised or painted steel, excessive fume may be produced which contains additional hazardous components, and may result in metal fume fever or other health effects. Arc Rays can injure eyes and burn skin. Electric shock can kill. The product and work surface will be hot during and after welding.

2.4 Additional Information

Product information

Potential Health Effects

INHALATION

May be harmful if inhaled. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic respiratory reaction.

Eye contact

Contact with eyes may cause irritation. Particulates may cause irritation due to mechanical abrasion. May cause eye irritation with susceptible persons.

INGESTION

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion

	may cause irritation to mucous membranes.
irritation	Repeated exposure may cause skin dryness or cracking.
sensitization	May cause sensitization of susceptible persons.
Chronic Effects Chronic Toxicity	Prolonged exposure may cause chronic effects. CNS and psychiatric effects, Parkinson-like symptoms. Languor, sleepiness and weakness in legs. A stolid masklike appearance of face, emotional disturbances such as uncontrollable laughter and spastic gait with tendency to fall in walking and findings in more advanced cases. Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Repeated or prolonged exposure may cause central nervous system damage.
carcinogenicity	This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).
Main Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Neurological disorders.
Aggravated Medical Conditions	Skin disorders, Neurological disorders, Respiratory disorders, Preexisting eye disorders, Allergies, Blood disorders, Kidney disorders, Liver disorders, Overexposure may cause female and male reproductive disorder(s)
Environmental Hazard	See section 12 for additional ecological information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Formula	CAS-No	Weight-%	GHS Classification
Nickel	Ni	7440-02-0	> 50	STOT RE 1 (H372) Resp. tract, inhalation Carc. 2 (H351) Inhalation Skin Sens. 1 (H317) S,7 Aquatic Chronic 3 (H412)
Chromium	Cr	7440-47-3	3 - 5	Not classified
Silicon Metal	Si	7440-21-3	1 - 2.5	Not classified
Boron	B	7440-42-8	0.1 - 1	Not classified

Note	This product may contain additional substances with a content of less than 0.1 % per substance, which are not listed. May contain additional substances in a range up to 2 % which are not classified hazardous or may not contribute to the products overall classification.
Full text of H-Statements referred to under sections 2 and 3	H228 - Flammable solid H317 - May cause an allergic skin reaction H351 - Suspected of causing cancer if inhaled H372 - Causes damage to the following organs through prolonged or repeated exposure if inhaled: Lungs H412 - Harmful to aquatic life with long lasting effects

4. FIRST AID MEASURES

General Advice Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.1 Description of first aid measures

Eye contact Keep eye wide open while rinsing. Call a physician immediately. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash off immediately with soap and plenty of water.

INHALATION Move to fresh air. Immediate medical attention is required. If not breathing, give artificial respiration.

INGESTION Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. Rinse mouth.

Self-Protection of the First Aider Wear suitable gloves. Self-Protection of the First Aider.

4.2. Most important symptoms and effects, both acute and delayed CNS and psychiatric effects, Parkinson-like symptoms. Languor, sleepiness and weakness in legs. A stolid masklike appearance of face, emotional disturbances such as uncontrollable laughter and spastic gait with tendency to fall in walking and findings in more advanced cases. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically. May cause sensitization by inhalation and skin contact.

Notes to physician Treat symptomatically May cause sensitization by inhalation and skin contact May cause sensitization of susceptible persons

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Extinguishing Media Which Must Not Be Used For Safety Reasons None.

5.2 Special hazards arising from the substance or mixture Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive and/or toxic fumes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. May cause sensitization by inhalation and skin contact. Carbon oxides.

5.3 Advice for fire- fighters Use personal protective equipment as required. In the event of fire, wear self-contained breathing apparatus.

Component information

Chemical Name	Extinguishing Media for Fires (Suitable)	Extinguishing Media for Fires (Unsuitable)
Chromium	Use extinguishing media appropriate for surrounding fire.	Do not use carbon dioxide, which may form an explosive mixture with powdered chromium.
Silicon Metal	SMALL FIRES: Dry chemical, sand, water spray, foam.; LARGE FIRES: Water spray, fog, foam	-

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with skin and eyes. Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust accumulation in enclosed space.

6.2 Environmental precautions Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Pick up and transfer to properly labeled containers. Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust.

6.4 Reference to other sections

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with eyes, skin and clothing. Wear suitable protective clothing. Use only with adequate ventilation. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place. Keep containers tightly closed in a cool, well-ventilated place.

Storage Temperature

Storage Life

Stable under normal conditions

Incompatible Materials

7.3 Specific end use(s)

Welding. Restricted to professional users. For use in industrial installations only.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Chemical Name	China	Hong Kong	India	Indonesia	Japan
Nickel	TWA: 1 mg/m ³ STEL: 2.5 mg/m ³	TWA: 1.5 mg/m ³	-	TWA: 1.5 mg/m ³	1 mg/m ³ OEL
Chromium	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³	TWA: 0.5 mg/m ³	-	TWA: 0.5 mg/m ³	0.5 mg/m ³ OEL
Silicon Metal	-	-	-	TWA: 10 mg/m ³	-
Chemical Name	Korea	Philippines	Singapore	Taiwan	Thailand
Nickel	TWA: 1 mg/m ³	1 mg/m ³ TWA	PEL: 1 mg/m ³	1 mg/m ³ TWA	-
Chromium	TWA: 0.5 mg/m ³	1 mg/m ³ TWA	PEL: 0.5 mg/m ³	1 mg/m ³ TWA	-
Silicon Metal	TWA: 10 mg/m ³	-	PEL: 10 mg/m ³	-	-
Chemical Name	Vietnam
Nickel	0.05 mg/m ³ TWA 0.25 mg/m ³ STEL	-	-	-	-

During Welding

If welding is performed on plated or coated materials such as galvanised or painted steel, excessive fume may be produced which contains additional hazardous components, and may result in metal fume fever or other health effects

8.2 Exposure controls

Personal Precautions

Use personal protective equipment as required. Avoid contact with eyes, skin and clothing. Wash hands before eating, drinking or smoking. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product.

Engineering Controls

Ensure adequate ventilation, especially in confined areas.

Eye protection

Wear safety glasses with side shields (or goggles).

Skin protection

Wear impervious gloves and/or clothing if needed to prevent contact with the material. Wear gloves according to EN 374 to protect against skin effects from powders. Always ensure

that gloves are free from defects and that they are stored and used correctly. Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves. Glove thickness ≥ 0.5 mm.

Hand protection	Protective gloves. The product and work surface will be hot during and after welding. Ensure adequate protection is in place to stop individuals from burning themselves.
Respiratory Protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. If exposure limits are likely to be exceeded or if irritation or other symptoms are experienced, NIOSH/MSHA or EN 136 approved respiratory protection should be worn. Wear a positive-pressure supplied-air respirator with full facepiece. Full-/Half-/quarter-face masks (DIN EN 136/140), P2, P3, FFP2, FFP3. Any supplied-air respirator that has a full facepiece and is operated in a pressure-demand or other positive pressure mode. Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20. High efficiency particulate air filter (HEPA filter).
Hygiene Measures	Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling. Wash hands before breaks and at the end of workday. Avoid contact with skin, eyes and clothing. Keep working clothes separately.
Special Precautions for Users	Eye-irrigation bottle with pure water. Health Surveillance should be in place for employees who are exposed while using this product. Training required.
Biological standards	
Environmental Exposure Controls	Do not allow to enter into soil/subsoil. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical State @20°C	Solid	appearance	Metallic, powder
particle size	~90 µm / 170 mesh	Odor	None
Melting Point / Melting Range	965-1040 °C / 1770-1900 °F	Flash Point	Not applicable
vapor pressure	Not applicable	vapor density	Not applicable
Water Solubility	Insoluble in water	Autoignition Temperature	N/A
Dynamic Viscosity	Solid	Density VALUE	8.44 g/cm3
Explosive Properties	Not applicable		

9.2. Other information

VOC content (%) Not applicable

Component information

Chemical Name	Mol. Weight	Water Solub.	Vap. Press.	Vap. Dens.	pH Val.	Autoign. Temp.	Evap. Rate	Boil. Temp.
Nickel	58.69 g/mol	-	1 mmHg at 1810 °C	-	-	-	-	-
Chromium	51.99 g/mol	-	-	-	-	-	-	2642 °C
Silicon Metal	28.08 g/mol	<1 mg/L	-	-	-	-	-	-
Boron	10.81 g/mol	-	0.0000156 atm at 2140 °C	-	-	-	-	-
Chemical Name	Density	Melt. Temp.	flash point	Water Sol.	Bulk Dens.	Odor	State	Color

	VALUE							
Nickel	8.9 g/cm ³ at 25 °C	-	-	insoluble	-	-	-	-
Chromium	7.19 g/cm ³ at 20 °C	1900 °C	-	insoluble	-	-	-	grey
Silicon Metal	2.33 g/cm ³ at 25 °C	1410 °C	-	-	-	-	-	dark grey; dark brown

10. STABILITY AND REACTIVITY

- 10.1 Reactivity** Stable under normal conditions.
- 10.2 Chemical stability** Stable under normal conditions
- 10.3 Possibility of hazardous reactions** Stable under normal conditions.
- 10.4 Conditions to avoid** Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
- 10.5 Incompatible materials** Acids. Strong oxidizing agents.
- 10.6 Hazardous decomposition products** Thermal decomposition can lead to release of toxic/corrosive gases and vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product information

Acute Toxicity	
INHALATION	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Eye contact	Contact with eyes may cause irritation. Particulates may cause irritation due to mechanical abrasion. May cause eye irritation with susceptible persons.
Skin Contact	Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Prolonged contact may cause redness and irritation. Prolonged skin contact may defat the skin and produce dermatitis. May cause sensitization by skin contact.
carcinogenicity	Category 2
Neurological Effects	Repeated or prolonged exposure may cause central nervous system damage. Prolonged or excessive exposure to manganese in dust or fume may cause irreversible central nervous system damage (Manganism). Symptoms resemble Parkinson's disease and include tremors, impaired speech, mask like face and impaired movement.
INGESTION	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea Ingestion may cause irritation to mucous membranes
irritation	Repeated exposure may cause skin dryness or cracking.
corrosivity	No information available
sensitization	May cause sensitization of susceptible persons

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel	>9000 mg/kg bw	Data waiving - Other Justification	NOAEC >=10.2 mg/L air
Chromium	LD50 >5000 mg/kg bw	Data waiving - Study Scientifically Unjustified	LC50 >5.41 mg/L air (analytical)
Silicon Metal	LD50 >3160 mg/kg bw	LD50 >5000 mg/kg bw	Acutely Non Toxic
Boron	650 mg/kg (Rat)	Not Listed in C&L Inventory	> 5.08 mg/l

Chronic Toxicity

Prolonged exposure may cause chronic effects. CNS and psychiatric effects, Parkinson-like symptoms. Languor, sleepiness and weakness in legs. A stolid masklike appearance of face, emotional disturbances such as uncontrollable laughter and spastic gait with tendency to fall in walking and findings in more advanced cases. Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Repeated or prolonged exposure may cause central nervous system damage.

carcinogenicity

This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Carcinogenic Effects

The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical Name	IARC	China - Carcinogens	India - Carcinogens	Indonesia - Carcinogens
Nickel	Nickel Compounds: Group 1 - Known Human Carcinogen - Nickel, Metallic & Alloy: Group 2B - Possible Human Carcinogen	Possibly carcinogenic to humans	-	-
Chromium	Group 3 - Not Classified as a Human Carcinogen	-	-	A4 - not classifiable as a human carcinogen
Chemical Name	Japan	Japan - ISHL Designated Carcinogens	Korea - Carcinogens	Philippines
Nickel	Group 1 Group 2B	-	2 - Limited evidence of human or animal carcinogenicity (metal, Serial No. 045)	-

Mutagenic effects

None known

Reproductive Toxicity

None known.

developmental toxicity

None known

Target Organ Effects

Blood, EYES, Jaw, Kidney, Liver, Lungs, Nasal cavities, Respiratory system, skin, Teeth

Neurological Effects

Repeated or prolonged exposure may cause central nervous system damage. Prolonged or excessive exposure to manganese in dust or fume may cause irreversible central nervous system damage (Manganism). Symptoms resemble Parkinson's disease and include tremors, impaired speech, mask like face and impaired movement.

11.2 Other Information

Substance related information

None

12. ECOLOGICAL INFORMATION

12.1. Ecotoxicity

ecotoxicity

Very toxic to aquatic organisms.

Chemical Name	Algae Toxicity	Acute Fish Toxicity	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Nickel	EC10 - 316.5 ug/L	LC50 - 15.3 mg/L	Not available	LC50 >200ug/L (@6-6.5 pH), 13ug/L (@8-8.5pH)
Chromium	Data Waiving - Study Scientifically Unjustified	Data Waiving - Study Scientifically Unjustified	Not available	Data Waiving - Study Scientifically Unjustified
Silicon Metal	Data Waiving - Study Scientifically Unjustified	Data Waiving - Other Justification	Not available	Data Waiving - Study Scientifically Unjustified

Boron	EC0 1 mg/l (72h, green algae)	LC0 >= 1mg/l (96h, Zebra fish)	-	EC0 >= 1 mg/l (48h, Daphnia)
-------	-------------------------------	--------------------------------	---	------------------------------

12.2 Persistence and degradability Product/Substance is inorganic. Not applicable.

12.3 Bioaccumulative potential This substance is not considered to be persistent, bioaccumulating nor toxic (PBT).

12.4 Mobility in soil No information available

12.5 Results of PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB

12.6 Other adverse effects

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

disposal considerations It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Improper disposal or reuse of this container may be dangerous and illegal. Refer to applicable local, state and federal regulations as well as industry standards.

Waste from Residues/Unused Products Reuse or recycle.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

other information Waste codes should be assigned by the user based on the application for which the product was used.

14. TRANSPORT INFORMATION

IMO / IMDG NOT REGULATED

ICAO / IATA-DGR NOT REGULATED

China (IECSC) NOT REGULATED

Australia Dangerous Goods NOT REGULATED

Japan NOT REGULATED

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other Regulations None

All of the components in the product are on the following Inventory lists

Chemical Name	China - Chemicals Regulated under National Standard (GB)	China - List of Dangerous Chemicals
Silicon Metal	-	Present (powder, amorphous)

Chemical Name	India - Hazardous and Toxic Chemicals	Japan - ISHL Disclosure cut-off list
Nickel	Present (powder)	>=0.1%
Chromium	Present (powder)	>=0.1%
Silicon Metal	-	Ignitable substance (listed under Metallic powder)
Boron	Present (powder)	-
Chemical Name	Korea - Substances to Control - Metals	Singapore - Hazardous Substances
Nickel	1 %	-
Chromium	1 %	-
Chemical Name	Thailand - Hazardous Substances	Vietnam - Chemicals
Nickel	-	1000 kg (inhalable powder)
Boron	-	2804 50 (Hazardous chemicals require chemical safety data sheets)

All of the components in the product are on the following inventory lists

Chemical Name	IECSC - China Inventory of Existing Chemical Substances	Inventory - Japan - Existing and New Chemical Substances (ENCS)	Inventory - Japan - Industrial Safety and Health Law Substances (ISHL)	Inventory - Korea - Existing Chemicals Inventory (KECI/KECL)	Inventory - Philippines - Inventory of Chemicals and Chemical Substances (PICCS)	Inventory - Taiwan - Taiwan Chemical Substance Inventory (TCSI)
Nickel	Present [25343]	-	-	Present [KE-25818]	Present	Present
Chromium	Present [13603]	-	-	Present [KE-05970]	Present	Present
Silicon Metal	Present [13814]	-	-	Present [KE-31029]	Present	Present
Boron	Present [25541]	-	-	Present [KE-03518]	Present	Present

15.2 Chemical Safety Assessment Chemical Safety Assessment available for this product.

16. OTHER INFORMATION

Global Automotive Declarable Substance List Classifications

Chemical Name	Global Automotive Declarable Substance List Classifications	Global Automotive Declarable Substance List Thresholds
Nickel	Declarable Substance (FI)	0.1 %

Prepared By Kennametal Inc. 1600 Technology Way Latrobe, PA 15650, USA

Issuing Date 2018-01-10

Revision date 2018-01-10

Revision note Not applicable

Disclaimer

Kennametal urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific SDSs, we are not and cannot be responsible for SDS's obtained from any source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version

End of Safety Data Sheet