

# HALLER

德国设计 欧洲品质 中国智造

GERMAN DESIGN

EUROPEAN QUALITY

BUILT IN CHINA



## 钻尖倒刃机 *Drill Edge Rounding Machine*

### HALLER-DER



## 特点 Features

- ◆ 便携式结构，轻便易搬动；
  - ◆ 双滑轨设计，扭矩马达传动，提升使用寿命和稳定性；
  - ◆ 智能PLC控制系统，高效灵活；
  - ◆ 半自动化操作，节省人力和人为误差；
  - ◆ 水平方向与垂直方向角度可调节，适用于各种钻尖；
  - ◆ 后拉式夹持设计，不易误触砂轮，安全性更高；
  - ◆ 钻尖快速180度换向，效率高，精度高；
  - ◆ 装夹快速定位，定位准，易操作；
  - ◆ 采用5C夹头（D3-25mm），可夹持范围广，支持夹头定制；
  - ◆ 支持总长50-450mm的刀具，适用旋转类所有刀具。
- ◆ Portable structure, easy to move;
  - ◆ Double slide design and torque motor ensure longer lifetime and better stability;
  - ◆ Intelligent PLC control system, high efficiency and flexibility;
  - ◆ Semi-automatic operation, saving labor and reducing personal errors;
  - ◆ Adjustable horizontal and vertical angles, applied for all kinds of drill points;
  - ◆ Back-pull clamping design, preventing accidental touch of wheel, higher safety;
  - ◆ 180° high-speed reverse of drill point, high efficiency and accuracy;
  - ◆ Fast positioning of clamping, accurate and easy operation;
  - ◆ Equipped with 5C collet (D3-25mm), applied for a wide range of tools. Customization for special size is available;
  - ◆ Applied for tools with a total length of 50-450mm, suitable for all rotary type of tools.

## 技术参数 Technical Data

外型尺寸: 长x宽x高 (含机脚)	Dimension: Length x Width x Height (Feet incl.)	580x325x330 mm
净重	Net weight	约(Appr.) 38 kg
抛光毛轮最大转速	Max speed of wheel	1350 rpm
Z 轴移动行程	Z-axis travel path	110 mm
X 轴最大可调行程	X-axis adjustable travel max	10 mm
夹头型号	Chuck type	5C
轮刷中心高度调节范围	Wheel brush center height adjustment range	-5 -15 mm
轮刷外径	Wheel brush diameter	D32 / D150 mm
粗磨速度范围	Rough grinding speed range	0.1-9.9 mm/s
精磨速度范围	Fine grinding speed range	0.1-9.9 mm/s
功率	Power	305 W
电源	Power supply	220VAC/50HZ

