

油式模温机规格参数:

项目	ITEM	单位UNIT	SGO-6	SGO-9	SGO-12	SGO-18	SGO-24	SGO-9D
温控范围	Temp control range	° C	进水温 Inlet water temperature+25° C~200° C					
温控精度	Temp control accuracg		PID±1° C					
电源	Power supplg		AC3 φ 380V 50HZ 3P +E					
传热媒体	Heat transferring medium		导热油 Conduction oil					
冷却方式	Cooling method		间接冷却 Indirect Cooling					
加热能力	Heating capacity	kw	6	9	12	18	24	9+9
泵浦马力	Horsepower of pump	hp	0.5	1	2	3	5	1+1
泵浦工作流量	Working flow of pump	l/min	35	56	95	190	240	56+56
泵浦工作压力	Working pressure of pump	kg/cm <sup>2</sup>	1.5	1.8	2	2.2	2.6	1.5
储油量	Oil reserve	liter	8	8	8	25	40	25
最大电力消耗	Maximum power consumption	kw	6.5	10	13.5	20.5	28	20
警报功能	Alarm function		缺相/缺水/超温/过载/反转 Open phase/water depletion/excess temperature/overloading/ reverse turn					
冷却水配管	Cooling water pipe	inch	1/2	1/2	1/2	1/2	1/2	1/2
循环水配管	Circulating water pipe	inch	3/8×2	3/8×4	3/8×4	3/8×4	(3/8×4)×2	(3/8×4)×2
外型尺寸	Size(L×W×H)	mm	650×325×745	650×325×745	650×325×745	1000×420×960	1000×420×960	650×450×1100
重量	Weight	kg	66	76	80	95	160	120

以上规格如有变更, . 恕不另行通知, 特殊规格可另行设计改造。The specifications above are subject to changes without notice. Some special specifications may be customized.